

GIRARD-PERREGAUX



USER MANUAL

TOURBILLON WITH THREE GOLD BRIDGES, 40 MM

INSTRUCTIONS FOR USE

WINDING

The self-winding system keeps your Tourbillon fully wound if you wear it at least 14 hours a day. If your Tourbillon has not been worn for some time, rewind it manually by turning the crown backwards and forwards when it is in position 0).

Warning: do not force the crown when resistance increases. When fully wound, the watch has a power reserve of approximately 50 hours.

SETTING THE TIME

1. Pull out the crown to position 1).
2. Turn the crown until the hour and minute hands are set 5 minutes before the exact time.
3. To set the seconds hand, first let the tourbillon cage turn until it reaches the 60-seconds mark, then hold it there by turning the crown very slightly in a counterclockwise direction.
At the time signal, move the minute hand forward until it has reached the exact time; then push the crown back into position 0). Your watch will then be synchronized and start immediately.

Warning: After making any setting, always return the crown to its original position, to preserve the water resistance of your watch and prevent any damage to the mechanism. To do so, press the crown against the case in the position 0).



FUNCTIONS

- a | Hours
- b | Minutes
- c | Tourbillon
- d | Small seconds on the tourbillon

GIRARD-PERREGAUX GP09600 SELF-WINDING MECHANICAL MOVEMENT

Diameter	32.00 mm (1 3/4''')
Height	6.87 mm
Frequency	21,600 Vib/h - (3 Hz)
Jewels	31
Power reserve	min. 50 hours
Displays	Tourbillon, hours, minutes, small seconds on the tourbillon

CASE

Diameter	40.00 mm
Height	11.55 mm
Crystal	antireflective sapphire
Case-back	see-through sapphire crystal
Water resistance	30 metres (3 ATM)

